



BOMAG
FAYAT GROUP

Rubber Tire Asphalt Paver **Cedarapids® CR652RX**




KEY FEATURES

- 16.7-ton hopper capacity
- Patented Remix Anti-Segregation System
- Outboard spreading auger drive
- Front gear box remix auger drive
- Independently controlled delivery and spreading augers
- Patented frame-raise system
- Three-point suspension system
- Maximum paving width of 30 ft (9.1 m)
- Maximum paving depth of 12 in (305 mm)
- Large Tire footprint



Technical Specifications

Cedarapids® CR652RX



Dimensions in inches (mm)

Clearance	A		B		C
	Screed	Auger Screed Up	Auger Screed Down	Frame	
Frame Raised	15.5 (394)	9 (229)	9.5 (241)	6.5 (165)	
Frame Lowered	9 (229)	3 (76)	5 (127)	8 (203)	

Standard Equipment

- Turbocharged 260 hp Tier 4i diesel engine
- Power-tilt hood with radiator
- Patented Remix Anti-Segregation System
- Lockout/tagout capable E-stop and master electrical switch
- Fume-recovery system
- Accessible filter locations
- All-welded mainframe construction
- Patented Frame Raise and Three-Point Suspension system
- Adjustable spreading auger height
- Outboard spreading auger drive
- Front gear box remix auger drive
- Independently controlled delivery and spreading augers
- Reinforced, sealed, tilting hopper wings with beveled corners
- Hydraulically adjustable screed vibrators
- Hydraulic power crown control
- Adjustable material retaining plates
- Oscillating front wheel bogie assemblies
- Hydraulic front wheel alignment
- Hydrostatic steering
- Operator's umbrella
- 30 ft hose reel for spray-down
- Back-up alarm

Mandatory Options (Select only one)

- Two-wheel drive **or** Front wheel assist
- Oscillating push rollers **or** Truck hitch

Optional Equipment

- Stretch® 20 screed with electric or oil heat
- Fastach® 10 screed with electric or oil heat
- Proportional steer assist
- Grade and slope control
- Multi-foot grade reference system
- Sonic averaging systems
- Bevel guide plates
- Cutoff shoes, 12" and 24" sections
- 500-hour filter kit
- Screed extensions
- Up time kit

Dimensions in inches (mm)

D	E	F	G	H	L1	L2
21 (533)	10 (254)	106 (2692)	90 (2286)	108 (2743)	250 (6350)	239 (6071)

Technical Data

Paver

Paver width	in (mm)	124 (3150)
Paving width (max)	ft (m)	30 (9.1)
Paving depth (max)	in (mm)	12 (305)
Paving speed (max)	ft/min (m/min)	426 (130)
Travel speed (max)	mph (kmph)	11.2 (18)
Drive tires		16-ply 24.5 x 32 in (622 x 813 mm)
Front wheels		16 in wide x 22 in dia (406 x 559 mm)
Brakes		multiple disc parking

Weights

Tractor	lbs (kg)	36200 (16420)
with Fastach® 10 and hydroflated tires	lbs (kg)	40200 (18234)
with Stretch® 20 and hydroflated tires	lbs (kg)	44100 (20003)

Engine

Engine manufacturer		Cummins
Type		QSB6.7
Tier Compliance		Tier 4i
Performance	hp (kW)	260 (194)
Speed	rpm	2200
Electrical	V	12

Capacities

Diesel fuel	gal (l)	72 (273)
Hydraulic oil	gal (l)	75 (284)
Cooling system	gal (l)	6.5 (25)

Spreading Auger Sections

Construction		Cast, high alloy
Diameter	in (mm)	16 (406)
Thickness	in (mm)	0.625 (16)

Hopper

Length and width	in (mm)	90 (2286) x 119 (3013)
Volume	ft ³ (m ³)	267 (7.56)
Capacity	tons (tonnes)	16.7 (15)
Feed tunnel width (each)	in (mm)	30 (762)
Remix augers (diameter)	in (mm)	12 (305)
Auger thickness	in (mm)	0.625 (16)
Trough liner thickness	in (mm)	0.375 (9.5)

Screed

Screed plate thickness	in (mm)	0.5 (12.7)
Positive crown (hydraulically powered)	in (mm)	3 (76)
Negative crown (hydraulically powered)	in (mm)	1 (25)
Vibrations per minute (max)		3000

Screed Heaters

Stretch® 20 (electric heat) generator	kW	34
Stretch® 20 (four oil heaters) 274,000 BTU (total) gph (lph)		2 (7.6)
Fastach® 10 (electric heat) generator	kW	34
Fastach® 10 (two oil heaters) 178,000 BTU (total) gph (lph)		1.3 (4.9)

Technical modifications reserved.
Machines may be shown with options.
*Weights are based on average shipping weights.



BOMAG Americas, Inc.
2000 Kentville Rd. • Kewanee, IL 61443
Tel: 309 853-3571 • Fax: 309 852-0350