



SUPERIOR

**EXCLUSIVELY
— FROM —
SUPERIOR**



TRAILBLAZER[®] CONVEYOR

36" / 42"

- **500-foot pre-assembled portable groundline conveyor** (including belting) transports from site to site in one 84-foot towable load.
- Compared to several transfer conveyors, a **single transfer point reduces maintenance** cleanup and power cable management.
- One conveyor drive and a single belt **reduces energy costs** produced by several transfer conveyors.
- Experienced crews can unfold/fold the 500-foot package in **as little as an hour**.

SPECIFICATIONS AND PHOTO GALLERY

OPERATING DIMENSIONS	36" BW	42" BW
Feed Height to Hopper (m)	4'-2" (1.3)	4'-2" (1.3)
Discharge Height to Center of Head Pulley (m)	12'-6" (3.8)	12'-6" (3.8)
Conveyor Length (m)	500'-0" (152.4)	500'-0" (152.4)
Tons per Hour (tonnes per hour)	1,000 (907)	1,500 (1,360)
TRAVEL DIMENSIONS		
Travel Length (m)	83'-3" (25.4)	86'-7" (26.4)
Travel Height (m)	14'-0" (4.3)	14'-0" (4.3)
Travel Width (m)	11'-4" (3.5)	11'-10" (3.6)
Weight at Axle (kg)	41,500 (18,824)	47,500 (21,545)
Weight at Kingpin (kg)	28,000 (12,700)	40,000 (18,143)



See video at bit.ly/trailblazer-conveyor