## P3500







SINGLE STAGE ROTARY FAN TYPE DETACHABLE SNOW BLOWER

## P3500 — TECHNICAL SPECIFICATIONS



**PERFORMANCE** 

Capacity<sup>1</sup>: Up to 4000 tons/hour
Projection<sup>1</sup>: Up to 39 m (130 ft)

**DIMENSIONS** 

Overall width: 2959 mm (116 ½ in.)
Overall height: 2895 mm (114 in.)
Working height: 1905 mm (75 in.)

• Weight: 7961 kg (17,550 lb) approx.

**IMPELLER** 

• Diameter: 1740 mm (68 ½ in.)

• Blades: Six (6) blades, 6 mm (1/4 in.) thick

• Rotation: 90° total

• Projection<sup>1</sup>: Up to 39 m (130 ft)

STANDARD HYDRAULIC STEERING VANES

• Height: 2273 mm (89 ½ in.)

**E**NGINE

• Type: 403 kW (540 hp) Turbo Diesel Tier 3 engine

• Block heater: 3000 W

FUEL TANK

• Type: Steel

• Capacity: 415 L (109 gal)

**HYDRAULIC SYSTEM** 

• Type: Hydraulic pump of 23 L/min (6 US GPM)

directly mounted on engine auxiliary drive

• Capacity: 19 L (5 gal)

**ELECTRICAL SYSTEM** 

• Alternator: 12 V, 150 A, sealed

• Batteries: Two (2) type 8D - 2000 CCA, maintenance

free

**DRIVELINE SYSTEM** 

Clutch: Twin Disc, model SP-314Gear box: One (1) bevel gear box

• Lubrification: Oil bath

• Safety mechanism: One (1) set of shear bolts protects the fan

**INSTRUMENT PANEL AND CONTROLS** 

Model: Heavy duty control and display system

PLUS +1 from Sauer Danfoss

• Controls: • One controller using a multiplex CAN

communication

◆ One high resolution grayscale LCD display

of 2 in. x 4½ in.

• One joystick with integrated functions

• One key ignition switch

**S**KATES AND SCRAPER BLADES

• Quantity: • Two (2) external skates

• Four (4) internal skates

• Type: Carbide skates

• Scraper blades: • Two (2) reversible scraper blades of 13 mm x 152 mm (½ in. x 6 in.)

• One (1) non-reversible scraper blade of

13 mm x 178 mm (½ in. x 7 in.)

**OPTIONAL EQUIPMENT** 

• 256 color LCD screen of 3\frac{1}{8} in. x 5\frac{3}{4} in.

• Carbide chrome 60Rc (drum)

• Low coolant level alarm

• Residential Cowl muffler

Wireless control system

• Wireless emergency engine shutdown system

 $^{1}$ Depending on snow conditions.

## www.rpmtechgroup.com





## R.P.M. TECH INC.

2220 Michelin Street Laval QC H7L 5C3 CANADA

Tel.: 450.687.3280 • Fax: 450.781.8811

Toll free: 1.800.631.9297 1.800.463.3882

Email: info@rpmtechgroup.com

2016.01 ~ RPM Tech Inc. reserves the right to change or discontinue any designs, specifications, features, models or accessories shown or indicated without notice.

Dealer