



VLB-98

VLB-98



PERFORMANCE¹

- Capacity: Up to 1600 tons/hour
- Projection: Up to 38 m (125 ft)

DIMENSIONS

- Overall width: 2489 - 2540 mm (98 - 100 in.)
- Overall height: 3050 mm (120 in.)
- Working height: 1220 mm (48 in.)
- Weight: 1470 kg (3240 lb)
- Weight HD version: 1606 kg (3540 lb)

CARRIER

- Power: Up to 131 kW (175 hp)
at 2200 rpm

DRIVELINE SYSTEM

- Power take-off: 1480 Series U-joints, rotating
at 1000 rpm
- Type: Chain and gear type reduction
- Lubrication: Oil bath
- Protection: By shear bolts

AUGERS

- Quantity: Two (2)
- Diameter: 508 mm (20 in.)
- Type: One piece ice type design,
bolted and interchangeable

IMPELLER

- Diameter: 865 mm (34 in.)
- Blades: Five (5) blades
- Rotation: 150° total, flat discharge
to the right

LOADING CHUTE

- Diameter: 305 mm (12 in.)
- Rotation: 270°

HEAVY-DUTY (HD) VERSION INCLUDES

- 9.5 mm (3/8 in.) augers
- Carbide inserts skates
- Overspill guards
- Hydraulically extendable loading chute
- Right side support for sidewalk shoulder,
including carbide shoes

OPTIONAL EQUIPMENT

- 457 mm (18 in.) chute extension
- CHT-400 bottom blade
- Double push arm
- Hydraulic steering vanes
- Reduction gear box 1000 rpm - 540 rpm

¹ Depending on snow conditions



ISO 9001:2008

QUEBEC CITY
184 Route 138
Cap-Santé, Quebec GOA 1L0
Telephone: 418.285.1811
Toll free: 1.800.463.3882
www.rpmttechgroup.com

LAVAL
2220 Michelin Street
Laval, Quebec H7L 5C3
Telephone: 450.687.3280
Toll free: 1.800.631.9297
info@rpmttechgroup.com

Specifications on this brochure may be changed without prior notice.
Revised : 2010.04