



# TRAKPACTOR 480

The Powerscreen® Trakpactor 480SR horizontal shaft impactor is designed for processing soft to medium-hard primary & secondary materials such as natural rock & construction derived materials like asphalt, recycling & demolition waste.

An optional SR section is fully detachable using quick release hydraulics and electrics.



## ✓ APPLICATIONS

### AGGREGATE



Blasted rock  
River rock

### RECYCLING




C & D waste  
Foundry waste

### MINING



Processed ores  
Processed minerals

[www.powerscreen.com](http://www.powerscreen.com)



## TECHNICAL HIGHLIGHTS

### INCREASED PRODUCTIVITY

- Highly aggressive chamber with 4 bar rotor / 2 aprons for high productivity.
- Start up motor for smooth engagement and increasing clutch life.
- Curved liners on feeder prevent material build-up.
- Direct drive via Desch gearbox provides better fuel efficiency.




### VERSATILITY

- Converts to Trakpactor 480 in minutes thanks to quick attach/detach SR section. Ideal for regions with transport weight restrictions.
- Recirculating conveyor slews hydraulically from recirculation to stockpiling mode.




### SERVICEABILITY

- Excellent access features for serviceability eg. hydraulic cabinet at ground level; unrestricted access to both sides of power unit; steel pipes in key locations.





# TECHNICAL SPECIFICATION



## 1 HOPPER

Length: 4.81m (15' 10")  
Width: 2.6m (8' 6")  
Capacity: 7.2m<sup>3</sup> (9.4 cu. yd.)  
Optional hopper extensions

## 2 CRUSHER

Feed Opening: 1270mm x 870mm (50" x 34")  
Min. CSS: 50mm (2") upper apron  
Max. CSS: 150mm (6") upper apron

## 3 BYPASS CONVEYOR (OPTION)

Width: 650mm (26")  
Discharge height: 2.59m (8' 6")

## 4 FEEDER

Vibrating grizzly feeder  
Length: 4.41m (14' 6")  
Width: 1.16m (3' 10")

## 5 TRACKS

Width: 500mm (1' 8")

## 6 POWER UNIT

Tier 2 Equivalent: Scania DC13 331kW (443hp)  
Tier 4F: Scania DC13 331kW (443hp)  
Stage V: Scania DC13 331kW (443hp)

## 7 TRAKPACTOR 480SR

All features of standard machine plus:

- 4.27m x 1.53m (14' x 5') double deck 2bearing screen, side tension media
- 1400mm (55") wide fines conveyor
- 500mm (20") wide cross conveyor
- 500mm (20") hydraulic folding recirc conveyor



# DIMENSIONS

## WORKING



## TRANSPORT

**Length:** 16.38m (53' 9")  
**Width:** 2.78m (9' 2")  
**Height:** 3.6m (11' 10")

## 480SR

**Length:** 19.05m (62' 6")  
**Width:** 3.6m (11' 10")  
**Height:** 3.33m (10' 11")

## WEIGHT

**Standard:** 47,750kg (105,270lbs)  
**480SR:** 56,150kg (125,112lbs)

## GET IN TOUCH

**Dungannon**  
200 Coalisland Road, Dungannon,  
Co Tyrone, BT71 4DR, Northern Ireland  
Tel: +44 (0) 28 87 718 500  
Fax: +44 (0) 28 87 747 231

**Louisville**  
11001 Electron Drive,  
Louisville, Kentucky, 40299 USA  
Tel: +1 502 736 5200  
Fax: +1 502 736 5202



[www.powerscreen.com](http://www.powerscreen.com)

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2023 Terex GB Limited. Published and Printed in November 2023.