



TITAN 2300

The Titan 2300 is a new secondary scalper designed for a wide range of applications. Capable of a 3-way or 2-way material split, this highly versatile screener can be operated as a standalone unit or as secondary scalper in a large variety of applications

The highly aggressive single shaft screenbox can provide up to 700tph (771 US tph) depending on the application making the Titan 2300 an extremely versatile machine in a lightweight and compact transport envelope



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING



Top Soil
C&D waste
Composed materials
Wood By-Products
Overburden
Foundry Waste

MINING



Processed ores
Processed minerals



TECHNICAL HIGHLIGHTS



- High capacity up to 700 tph / 771 US tph (depending on media sizes & material type)



- Titan 2300 boasts the widest feed conveyor (1500mm / 60") in the Powerscreen mobile screener range with a heavy duty twin gearbox drive

- Highly aggressive 6.1m x 1.83m (20' x 6') screenbox running at up to 5G force



- Excellent stockpiling capacity in a lightweight and compact transport envelope


- Titan 2300 has been designed with generous material transfer zones, optimising it for large volumes of material flow in applications such as biomass



- CAT C4.4 129 kW (173hp) engine across all applications running at 2200rpm which minimises fuel burn with the option for Dual Power available



TECHNICAL SPECIFICATION



1 FEEDER/HOPPER

6.2m³ (8.1 cu. yd) hopper capacity / 11m³ (14.4 cu. yd) with extensions
Optional hydraulic folding hopper extensions
1500mm (60") belt feeder
Heavy duty Toughflex belt option available for secondary scalping applications

2 SCREENBOX

6.1m (20') x 1.83m (6') 2 deck screen
Highly aggressive single shaft 2 deck, 2 bearing screen drive
Adjustable stroke and speed
Adjustable screen angle between 13° - 17°

3 OVERSIZE TAIL CONVEYOR

Width: 1600mm (64")
3.85m (12' 8") stockpile height
Adjustable angle and variable speed control

4 FINE SIZE SIDE CONVEYOR

Width: 1400mm (56")
Single tear-drop scraper as standard

5 MIDSIZE & FINESIZE SIDE CONVEYOR

Width: 1050mm (42")
4.1m (13' 5") stockpile height
Variable speed control
Hydraulically folding and angle adjustable

6 POWER UNIT

Tier 4F/Stage V: CAT C4.4 129kW (173hp)
@2200rpm
336L (89 US Gal) fuel tank
450L (199 US Gal) hydraulic oil tank



DIMENSIONS

WORKING



16,500mm (54' 3")

4,930mm (16' 2")



15,360mm (50' 5")

4,930mm (16' 2")

TRANSPORT

Length: 18.2 m (59' 10")
Width: 3m (9' 11")
Height: 3.6m (11' 10")

WEIGHT

Total Weight: 37,000kg (81,571lbs)

GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2023 Terex GB Limited. Published and Printed in July 2023.